

Pre-Configured Model: 28611



This Pre-configured model is made up of:

- 3 slot casing (code:28605)
- Function Generator (code:28610)
- Variable Power Supply (code:28603)

SPECIFICATIONS	
Input	220-240VAC 50Hz
Output DC Voltage	0-20VDC 0-1A Regulated
Load Regulation	0.02% + 2mV
Line Regulation	0.02% + 2mV
Ripple and Noise	10mV (rms)
Digital Display	3 Digit
Voltage Display Accuracy	-0.5% reading + 1 digit
Current Display Accuracy	-0.5% reading + 1 digit
Temperature Coefficient V	0.1% + 2mV/deg C
Temperature Coefficient A	0.1% + 2mV/deg C
Temperature Range	0 - 35 C
Duty Factor	100%
DC Offset	+10V to -10V(open circuit)
Frequency Ranges	10 Hz to 100 Hz
	100Hz to 1KHz
	1 KHz to 10KHz
	10KHz to 100KHz
Frequency Setting	100:1
Sine, triangle and square output	Amplitude 15V p-p
Sine wave distortion	Less than 3% from 10Hz to 100KHz
Output Impedence	50 Ω + 10%
Dimensions (mm)	220x182x155
Weight (kg)	2.8Kg