






USB PC cable for connection to the USB interface of a PC length 2.5 m, for communication with SIMOCODE pro or SIRIUS 3RW44 soft starter or safety system 3SK2 and 3RK3 via the system interface




**General technical data**

product brand name	SIRIUS
product designation	USB PC cable
ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C

**Certificates/ approvals**

General Product Approval	EMV	Test Certificates	Marine / Shipping
<a href="#">Confirmation</a>			  

**Marine / Shipping**    other

	<a href="#">Confirmation</a>
---	------------------------------

**Further information**

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>  
 Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7941-0AA00-0>  
 Cax online generator  
<http://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=3UF7941-0AA00-0>  
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3UF7941-0AA00-0>  
 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF7941-0AA00-0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7941-0AA00-0&lang=en)

