

## AN-CB5313-RA2

700 TVL Outdoor EXIR Bullet Camera



### Key Features


- 700TVL high resolution
- EXIR 40m
- Smart IR
- IP66 rating
- True day/night
- 0.1 Lux(0 Lux with IR)

### Specification

### Applications



### Dimension



### Model

**AN-CB5313-RA2**

<b>Camera</b>	Image Sensor:	1/4" Super CMOS
	Signal System:	PAL/NTSC
	Effective Pixels:	976(H)×496(V)
	Min. Illumination:	0.1 Lux @ (F1.2,AGC ON),0 Lux with IR
	Shutter Time:	1/25(1/30) s to 1/10,000 s
	Lens:	6mm (8mm optional)
	Lens Mount:	M12
	Day& Night:	IR cut filter with auto switch
	Horizontal Resolution:	700 TVL
	Synchronization:	Internal Synchronization
	Video Output:	1Vp-p Composite Output (75Ω/BNC)
	S/N Ratio:	More than 50dB
<b>General</b>	Operating Conditions:	-20 °C ~ 50 °C
		Humidity 90% or less (non-condensing)
	Power Supply:	12 V DC±10%
	Power Consumption:	Max 1.5 W
	Weather Proof:	IP66
	IR Range:	Approx 35 to 40 meters
Dimension:	150×80×65mm	