

TRONCONNECT LAN CAT6e FTP



Category 6 enhanced, overall foil screened twisted pairs

Used in the secondary and tertiary network level for the implementation of services such as



Application

Gigabit Ethernet, Fast Ethernet, Ethernet etc. The foils screen shields the cable from EMI and the cable is therefore suitable for use in tight cable channels and near power cables or machinery.

Technical Data

Ethernet LAN cable per ISO/IEC 11801 TIA/EIA 5688.2



TEMPERATURES

Operating: -20°C to 70°C



VOLTAGE RATING

Operating: 250V

Test: 1,500V



MIN. BENDING RADIUS

8 x OD



IMPEDANCE

100 (±15) Ω



CAPACITANCE

56 nF/km



TENSILE STRENGTH

13.8 Mpa



RESISTANCE (AT 20°C)

Insulation: > 20 MΩ/km

Electrical: < 74 Ω/km

Construction

F/UTP 4 x 2 x 24AWG

Annealed bare copper conductors (0.51mm ø)

or Copper clad aluminium conductors (0.55mm ø)

Core insulation with high density, low molecular weight, polyethylene compound (LDPE) (OD: 0.9mm (±0.05mm))

Twisted pairs assembled around a cross-filler

Solid tinned copper drain wire (Cu version) or copper clad aluminium (CCA version).

Screened with aluminium/polyester foil tape (100% coverage with 25% overlap)

Outer sheath with special 90°C PVC (RoHS compliant) (OD: 5.8mm (±0.2mm))

Nylon rip cord

Properties & Identification

Flame retardant as per IEC 60332-41

Available in solid or stranded bare copper as well as solid or stranded copper clad aluminium conductors.

Standard outer sheath colour Grey RAL 7001

Additional colours available on request: x = Grey (GY), Blue (BU), Green (GN), Yellow (YE), Red (RD), White (WH).

Also available in Black outer sheath with UV Protection

Additional

Cable marking: TRONCONNECT DATA CABLE FTP CAT6E 4PAIR 24AWG
ISO/IEC 11801 TIA/EIA 5688.2 (Meter marked)

PART NO.	NO. CORES X SIZE (AWG)	DESCRIPTION	CABLE OD	DRUM WEIGHT (KG/KM)
CAT6EFTP-x	4 x 2 x 24AWG	Cat6e FTP SOLID PURE COPPER	5.8	49.0
CAT6FTP-x	4 x 2 x 24AWG	Cat6e FTP SOLID CCA	5.5	38.0
CAT6EFTPS-x	4 x 2 x 24AWG	Cat6e FTP STRANDED PURE COPPER	6.2	44.0
CAT6FTPS-x	4 x 2 x 24AWG	Cat6e FTP STRANDED CCA	6.0	35.0

Accessories

Connectors: RJ45 Cat6 Shielded
Part no. RJ456EFTP-CL



Surface Mount: RJ45 Cat6 FTP
Part no. SMBD6EFTP-x

Boots: RJ45 Colour Coded
Part no. RJ456EBT-x



Patch Cords: Cat6 STP
Pure Copper or CCA

Inline Connectors: RJ45 Shielded
Part no. RJ456INLINE



Glue Stick: 40 x 11mm Clear
Part no. GLUESTICK