

## HD combine tester V70



<b>Analog SD and HD test</b>	
Signal Format	NTSC/PAL/*HD-CVI3.0/*AHD3.0/*HD-TVI3.0
Signal Level	1Vpp,
<b>12V Power Output</b>	
Power Output	12V/1A Output Interface : Circular outer diameter 4mm, Inner needle 1.6mm
<b>Audio Test</b>	
Audio Test	A audio signal input
<b>Coaxial PTZ Control test</b>	
Communication interface	Video IN BNC interface
Communication protocols	*CVI (dahua coax) *AHD (Pelco c) *TVI (Hikvision) *UTC (SD-UTC)
<b>RS485 PTZ Control test</b>	
Communication interface	RS485
Communication protocols	Pelco-D/P, Samsung, Panasonic, Lilin, Yaan... more than 30 protocols
Baud rate	150, 300, 600, 1200, 2400, 4800, 9600, 19200bps
<b>LED torch</b>	
Three LED	Three 35lm LED , can tun on individually when device is off
<b>Power</b>	
Charger	Micro USB 5v1A charge
Battery	18650 lithium battery*2, capacity 2000 mAh*2, working time about 8 hours
<b>System Specification</b>	
Display	4.3 inch TFT 480*272 resolution, 262K color, back light level adjustable
Operation	Power button, main control keypad of 8 keys, LED push switch *3
Setting	Chinese, English, user optional
Keyboard tone	On/Off
<b>Working environment and specification</b>	

Working temperature	-10°C---+55°C
Working humidity	30%-90%
Device Dimension	120*30*95mm
Weight	0.3kg(device with battery)