


针位排布图
 Contact arrangement



技术参数:

- 产品系列: M12 D-Code
 - 插针数: 4
 - 额定电流(40℃): 4A
 - 额定电压: 250V
 - 额定脉冲电压: 2500V
 - 污染等级: 3
 - 接触电阻: ≤10mΩ
 - 防护等级: IP67
 - 插拔次数: >100
 - 温度范围: -40℃...+85℃
 - 绝缘阻抗: ≥100MΩ
 - 接线方式: 螺钉锁紧
 - 线径范围: max.0.75mm² (max.AWG18)
 - 锁紧扭矩: 0.2Nm (螺钉接线)
 - 电缆直径: 4-6mm, 6-8mm
 - 电缆剥线长度: 20mm
 - 导线剥线长度: 5mm
- 材料特性:
- 锁紧螺帽: 金属
 - 插针材料: 铜合金
 - 插针表面处理: 镀金
 - 外壳材料: 锌合金
 - 绝缘材料: PA

Technical specification:

- Series: M12 D-Code
 - Number of contacts: 4
 - Rated current(40℃): 4A
 - Rated voltage: 250V
 - Rated impulse voltage: 2500V
 - Pollution degree: 3
 - Contact resistance: ≤10mΩ
 - Degree of protectio: IP67
 - Mating cycles: >100
 - Temperature range: -40℃ - +85℃
 - Insulation resistance: ≥100MΩ
 - Termination method: screw connection
 - Wire gauge: max.0.75mm² (max.AWG18)
 - Torque: 0.2Nm (screw terminal blocks)
 - Cable Outlet: 4-6mm, 6-8mm
 - Stripping length of the sheath: 20mm
 - Stripping length of the individual wire:5mm
- Material properties :
- Material of locking system: Metal
 - Material of contact: copper alloy
 - Contact plating: Au
 - Material of housing : Zinc die-cast
 - Material of Insert: PA

Standards: IEC 61076-2-101

符合标准: IEC 61076-2-101

						表面处理 Finish		-		图号 Drawing No.		-	
						材料 Material		-		产品代号 Part Code		M12-F04D-T-D8-SH	
标记 Mark		处数 Number		变更描述/Description				签名 Signature		日期 Date		产品料号 Part No.	
												1632044212002	
绘图 Drawn		姓名/Name		日期/Date		姓名/Name		日期/Date		比例 Scale		版本 REV.	
审核 Checked		ZQ XU		18.08.2016		-		-		1:1		V1.0	
工艺 Process		-		-		批准 Approved		YY LUO		18.08.2016		重量 Weight	
										数量 Qty.		57.3g	
										All Dimensions in mm Original Size DIN A 4		产品名称 Part Name	
												-	
												厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	