

SS40P Single-pole surge arrester

Class 2 arrester for installation in the LPZ OB - 1 Lightning Protection Zone in accordance with IEC 61643-1

Features

- High energy zinc oxide varistor
- Replaceable surge module
- Fault disconnect device
- Fault indication
- Fast response time
- Compact design



Specifications	12-00232
Rated voltage	275VAC
Nominal discharge current (8/20)	20kA
Maximum discharge current (8/20)	40kA
Voltage protection level at 5kA (8/20)	<1kV
Voltage protection level at Isn	<1.5kV
Response time	<25nS
Backup fuse (only required if not already provided in mains)	100A gL/gG
Short circuit withstand capability with maximum backup fuse	25kA / 50Hz
Operating temperature range	-40°C to +80°C
Mounting on	35mm DIN rail
Enclosure material	Grey thermoplastic
Degree of protection	IP20
Installation width	18mm
Tested in accordance to	IEC 61643-1

Designed and Manufactured by:

Clearline Protection Systems (Pty) Ltd

Roan Crescent Corporate Park North, Old Pta Road, Midrand, South Africa

P.O. Box 5985, Halfway House, 1685

Tel: +27 (0) 11 848-1111

Fax: +27 (0) 11 314-3880

E-mail: sales@clearline.co.za

www.clearline.co.za