

TV / Satellite Protection

Features

- Plug and play concept
- Easy installation
- Compact design
- Protects power, T.V. And satellite signals



This combination protector utilizes Clearline's equipotential platform technology for effective protection. The power protector includes failsafe current and thermal monitoring with visual and audible indication showing the status of the protection device. Various data protection modules are available.

Specifications

Power module

Max continuous voltage	250V 50Hz
Max continuous current	16A
Max discharge current ismax (8/20)	8kA L-N, L-E, N-E
Residual voltage at ismax (8/20)	Approx. 900V
Response time	<25ns
Filtration	>60dB
Standards compliance	IEC 99.4, ANSI C62.42,

Data module

	Satellite	TV
Max discharge current ismax (8/20)	10kA	10kA
Residual voltage at ismax (8/20)	<100V	<100V, L-L, L-E
Useable frequency	3 GHz	800MHz
Response time	10ns	<100ns

Designed and Manufactured by:

Clearline Protection Systems (Pty) Ltd

385 Roan Crescent Corporate Park North, Old Pta Road,
Midrand, South Africa

P.O. Box 5985, Halfway House, 1685

Tel: +27 (0) 11 848-1100

Fax: +27 (0) 11 314-3880

E-mail: info@clearline.co.za

www.clearline.co.za