

THE POWERLINE SERIES

12-00715

Mini Econo PABX Filter

Features

- Built in surge suppression
- High surge capability
- Compact design
- Effective filtration



The mini econo-pabx filter was designed to be more compact and cost effective solution to the standard pabx filter. The unit has a single stage filter capable of up to 30dB of attenuation of noise.

Also included is our standard surge module that will disconnect the load from the mains in the event of a fault thus preventing fire.

Another feature is the indication board that will notify the user when power is connected.

Specifications	
Max. continuous voltage	230V 50Hz
Max continuous current	10A
Earth leakage current	0.05mA
Nom. discharge current ismax (8/20)	5kA
Max discharge current Ismax (8/20)	5kA
Residual Voltage at 5kA (8/20)	±900V
Response time	<25ns
Max Filtration	30dB at 100kHz
Temperature range	-20°C to + 70°C
Standards compliance	IEC 61643-1

Designed and Manufactured by:

Clearline Protection Systems (Pty) Ltd

Roan Crescent Corporate Park North, Old Pta Road, Midrand, South Africa

P.O. Box 5985, Halfway House, 1685

Tel: +27 (0) 11 848-1100

Fax: +27 (0) 11 314-3880

E-mail: sales@clearline.co.za

www.clearline.co.za

