

# CS-C3U-22ER

1080p Weatherproof PoE Bullet IP Camera



## Main Features



Up to 2 megapixel (1920 × 1080) resolution



High-performance and long service life  
Infrared LED, up to 100 feet IR range



POE (Power over Ethernet)



IP66 weatherproof

## Specifications

Model	CS-C3U-22ER
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.028Lux @ (F2.0, AGC ON), 0 lux with IR
Shutter Time	1/3s to 1/100,000 s
Lens	4mm
	View Angle: 85°(horizontal)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR

Image	
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Backlight compensation	Yes, zone optional
Network	
Network Storage	Only support EZVIZ NVR
Interface	
Communication Inter- face	1 RJ45 10M/100M Ethernet interface
Reset Button	Yes
General	
Working Temperature/ Humidity	-22 °F to 140 °F (-30 °C to 60 °C) Humidity 95% or less (non-condensing)
Power Supply	PoE (802.3af)
Power Consumption	5W MAX (Max. 7 W as IR cut filter on)
Weather Proof Ratings	IP66
IR Range	Up to 100 feet (30m)
Dimension	Φ2.75" ×6.20"( Φ70×157.4 mm)
Weight	0.84 lb (380 g)

## Component (CS-NB-EU)

Item No.	Basic Equipment	Number	Unit	Product Image (The picture is only for reference)
1	Camera Model: CS-C3U-22R (4mm)	1	PCS	
2	Network Cable (RJ45 -to- RJ45, Cat5e UTP, CCA, 30m)	1	PCS	
3	Mounting Screws and Plugs (3_PA4×25-SUS)	1	PCS	
4	Mounting Templates	1	PCS	
5	Installation Guide	1	PCS	/
6	Warranty Card	1	PCS	/

## Dimension

