


Shorting Links

Ø1mm Shorting Link Plugs

- Choice of insulated or un-insulated links.
- Insulated links supplied in a variety of colours, with a high-performance gold finish.
- Un-insulated links can be soldered directly into the PCB for permanent linking.
- Can be used with PCB sockets (page 172) for hardware programming applications.



INSULATED	SPECIFICATION
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Style 1</p> </div> <div style="text-align: center;"> <p>Style 2</p> </div> </div>	<p>Material</p> <p>Moulding: PBT UL94V-0 Contact: Brass Finish: Insulated: Gold Un-insulated: See order code</p> <p>Electrical</p> <p>Current rating: 10A at 20°C</p>
<p>UN-INSULATED</p>	

HOW TO ORDER

D308 X - XX

SERIES CODE

TYPE		STYLE	PITCH (A)
0	Un-insulated	n/a	5.08mm
1	Un-insulated	n/a	6.35mm
2	Un-insulated	n/a	10.16mm
6	Insulated	1	5.08mm
7	Insulated	1	6.35mm
8	Insulated	2	10.16mm
9	Insulated	2	12.70mm

FINISH

05	Gold (un-insulated)	
46	Tin (un-insulated)	
97	Blue (insulated)	
98	Black (insulated)	
99	Red (insulated)	

All dimensions in mm.