

with 2 X USB Sockets 1 x Euro Socket / 1 x Contour Socket / 2 x USB Sockets / 2 x 3 Pin Sockets 250V ~ 16A

High Surge Protection



Repair or Replace warranty terms and conditions apply.

Overview

Don't risk losing your valuable equipment through a surge, protect it with the 4 Way Surge Secure Power Protector with 2 X USB Sockets. It has a built-in mains tester (see LED indicator lights) which checks that the wiring in the wall socket is safe to use or if there are possible wiring faults, as well as checking that the plug is working correctly. Quicker reaction time ensures full protection from power surges. This product does not protect against direct lightning strikes.



FIRE RESISTANT

Manufactured with flame retardant materials. Tested to the highest South African standards.

Packaging Dimensions

Height 347mm Weight 0.6 kg Depth 66mm Qty Width 88mm

Packaging Contents

1 x 4 Way Surge Secure Power Protector with 2 X USB Sockets

1 x Surge warranty form

The Ellies warranty is only valid for the Surge Secure Power Protector product if it is used in South Africa and for domestic use only.

Product Code: FBWP4U Barcode: 6002844073695

(6) Bulk Barcode: 16002844073692 (36) Bulk Barcode: 26002844073699

Mains tester LED indicators

Surge Secure Power Protector Plug has a built-in mains checker, which indicates if there are possible wiring faults. Indicator lights show that the Surge Protector is working correctly.



▼ Illuminated ■ Non-illuminated

If all the Surge Secure plug lights are OFF when the wall socket switch is **OFF**, then switch **ON** the wall socket switch and the following applies:



Correct Surge Secure



No earth



No live



Live and neutral reversed

If any of the Surge Secure plug lights are ON when the wall socket switch is **OFF**, then switch **ON** the wall socket switch and the following applies:



reversed

Live and earth



Faulty neutral



Live and neutral reversed



Faulty earth



Overload circuit fused wires

Max total combined surge current (Amps)	18 000 - 24 000
Max total combined surge energy (Joules)	500 - 700
Protection component response time (nSec)	< 25

Max connected load: 3680W