

		ODOOT OHLLT		
Flash Item No.:				
Previous Flash Code:				
Description				
200W SMD LED SLIN	FLOODLIGHT			
Auxiliary code: BL/ZR-TG200				
Barcode:	6009696370835			
Sample required when manufactured		YES		
for the first time	1.20			
Dimensions				
Length	386mm		1	
Width /Diameter	312mm		ARTWORK/PACKING SPE	CIFICATIONS
Depth	96mm ———————————————————————————————————		Product History	Existing
			Packing	Box Packing
Specifications:	Rated		Purpose	Display
Driver / Ballast	Intergrated CC Driver		Manual Required	Yes
IC Chip	0.75			Minimum Size Euro Hole - Flash Standard
Mains wire	0,75mm ² 3 Core pure copper cable		Euro Hole Required	No 3mm 7mm
Watt	200W			30mm
Lumen	15000lm		PLEASE COMPLETE ALL SHADED AREAS	
Colour Beam Angle	Matt Balck 120°		FOR ARTWORK PUR Length	POSES 403mm
Power Factor	> = 0,5		Width / Diameter	322mm
Voltage	230V 50Hz		Lid	113mm
Lifetime	3 years		Specifications	
IP Rating	IP65	OIX	Energy Rating Watt	A 200W
Colour Temp	6000K Daylight 6000K - 6500K		Lumen	15000lm
Rating Label Symbols		Colour Temp	6000K Daylight	
-	Flash Logo	0,5m ()	IP Rating	IP65
	Item No: 230V 50Hz		ADDITIONAL INFORMATION	
	200W,IP65		ICONS: BEAM ANGLE, RECYCLE, NO BIN, CE. IP65 SLOGANS: WARNINGS: REFER TO INSTRUCTION BEFORE INSTALLATION	
	-6000K Daylight			
	Production No: As per Order			
Packing per Export Carton			Earth wire to be connected .Failure to do so will void the Guarantee	
UV Laminated Finish	As per Flash Artwork		EXPORT CARTON SIDE MARKS	
Colour Box packing	SHIRNK PACK	EXPORT CARTON QTY	Quantity	
1 Pc	NO	2	Weights and Measurements	
Protection in packing	As per Flash instruction	Virgin Material Only	Carton 1-Up	
			Production No	
			Line drawing of lamp on 2 sides of export carton	
			Flash Guarantee must cover 70% of F printed in Red & Black as pe	
			Slogan must be printed in Red on 2 sides as per Flash Artwork	
			Use Virgin Material Only	
			SPECIAL INSTRUCTIONS	
			MUST BE FITTED WITH 30CM 3 CORE WIRE, STRIPPED AND	
			READY FOR TERMIN	
			BLACK GLASS PRINTED WITH WHITE AND IP RATING	
		<u>I</u>	AND II KATING	-