

## Give your gates more freedom to swing





take control of your world

## Introducing the all new 90 Blue swing gate operator



The 90 Blue swing gate operator - giving your gates more freedom to swing



take control of your world

## 90 Blue - Accessories and technical specifications:

CONTROL UNIT*	CONTROL CARD FEATURES	BLUE-I SAFETY BEAMS**	Description  Operating voltage 12 to 24 AC or DC  Surface mount Sealed lens 10 metre range Selectable normally open/normally closed relay output	
	Double swing control card 24volt DC motor output • onboard receiver for pedestrian and full opening operation (6 pedestrian and 25 full opening locations) • pedestrian and full opening inputs • onboard LED inputs indication • external LED status indication output • safety beam input • anti-crushing sensing • autoclose function adjustable 5 to 25 seconds • autoclose override feature • selectable pillar light/gate lock connection via onboard relay • gate leaf delay function • auxillary output 12 voltDC 200ma  Unique feature: Open and close limit switch inputs for the new magnetic type limit switches fitted to the 90 Blue motors			
90 BLUE SWING GATE OPERATOR		90 BLUE TECHNICAL SPECIFICATIONS		
		POWER OF MOTOR: 24V		24Vdc 60W
		CURRENT DRAW:		2.5 A
		MOTOR ROTATIONAL SPEED:		1500RPM
		SCREW ROD TRAVEL SPEED:		1.6cm/second
		SCREW ROD MAX TRAVEL:		300mm
		LIMIT SWITCH TYPE:		Magnetic
		MAX GATE LEAF LENGTH:		2 Meters
		OPERATIONS PER DAY:		30
	SWING GATE OPERATOR	ENVIRONMENT OPERATING TEMPERATURES:		-20°C / +55°C
		PROTECTION CLASS RATING:		IP 44
ET BLUE PLUS TRANSMITTERS**	ET BLUE PLUS TRANSMITTER FEATURES			
	<ul> <li>The 90 Blue swing gate operator is fully compatible with all ET Blue Plus transmitters</li> <li>Unique programming of additional rolling-code remotes, by the end user</li> <li>1, 2, 4 and 6 button options available</li> </ul>	Distributed by:  SYSTEMS SECURITY PRODUCTS SPECIALISTS  0860 109 238 www.et.co.za		

\*Included in kit. \*\*Optional extras.



take control of your world