


技术参数:

- 材料: 压铸锌
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 铁镀锌
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M20

Technical specification:

- Material: zinc die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - Locking type: single locking latch
 - material: steel lever with zinc plated
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M20

| | | | | | | | | | | | |
|---------------|--------------|------------------|----------------|----------------|------------|---|------------|---|------------|-------------------|--|
| | | | | 表面处理 Finish | | - | | 图号 Drawing No. | | - | |
| | | | | 材料 Material | | - | | 产品代号 Part Code | | H3A-SF-1L/W-M20 | |
| 标记 Mark | 处数 Number | 变更描述/Description | | 姓名/Name | 日期/Date | | | 产品料号 Part No. | | 1100032241002 | |
| 绘图 Drawn | BQ LUO | 04.17.2018 | 标准化 Stand. | - | - | 比例 Scale | 版本 REV. | 重量 Weight | 数量 Qty. | 产品名称 Part Name | |
| 审核 Checked | P RAO | 04.17.2018 | | | | 1:1 | V1.1 | 80g | - | - | |
| 工艺 Process | - | - | 批准 Approved | YY LIN | 04.17.2018 | All Dimensions in mm Original Size DIN A 4 | |  厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD | | | |