

**Description** : HelaCon Releasable connectors are used for fast, easy and reliable connection and distribution of cable and conductors in electrical installation applications.

**Features and Benefits** Universal push-in wire connector for solid, stranded and fine-stranded wires

Compact size connector  
 Wire clamping range: 0.2 - 4.0 mm<sup>2</sup>  
 Separate voltage test entry on the top  
 For proper fixing that can be visually checked through transparent housing  
 Safe application, installation and maintenance

**Technical Data**

Housing material : Polycarbonat (PC)  
 Spring material : Stainless Steel  
 Plate material : Tin-plated copper

Nominal current : 32 A

Nominal voltage (IEC) : 450 V

Cable diameter (IEC) : 0.2 - 4.0 mm<sup>2</sup>

Cable diameter (cULus) : 28 - 14 AWG



Type	Color	Length (L)	Width (W)	Height (H)	Pack Cont	Article No.
HCRN-2	Transparent(CL)	12mm	20,5mm	14mm	80	148-90059
HCRN-3	Transparent(CL)	17mm	20,5mm	14mm	50	148-90060
HCRN-5	Transparent(CL)	26mm	20,5mm	14mm	30	148-90061
HCRN-2	Transparent(CL)	12mm	20,5mm	14mm	10	148-90062
HCRN-3	Transparent(CL)	17mm	20,5mm	14mm	8	148-90063
HCRN-5	Transparent(CL)	26mm	20,5mm	14mm	5	148-90064

Operating temperature	up to +85°C (IEC) up to +105°C (cULus)
Stripping length	: 10 mm
Flammability	according to UL94 V0
Approvals / certificates	CE CULus, ENEC, EN60998-2-2:2004 (Intertek Semko AS, SGS Finko Ltd) EN 60998-2-2