



Hanlong Industrial Co., LTD

Tools MFR Since 1978



Products > Crimping Tools > Ratchet Crimping Tool > HT-336FM series

» Home Products

» Products

» Modular Crimping Tool

» Compression Tool

» Crimping Tool

» Stripper

» Cutter & Stripper

» Punch Down Tool

» Cable Tie Fasten Tool

» Fiber Optic Tool

» Tool Kit

» Others Tools

» About Us

» Contact Us
























336 series

- Die sets are interchangeable, except HT-301
- OEM/Custom designs are welcome

	Type no HT-	Die P/N	Specifications	Crimping cable size
	5133A 336A	3A	.256"/.068"/.213" 6.50/1.73/5.41mm	RG58, 59, 62
	5133A4 336A4	3A4	.255"/.187"/.068"/.213" 6.48/4.75/1.73/5.41mm	RG58, 59, 62, 174
	5133C 336C	3C	.256"/.319"/.068"/.213" 6.50/8.10/1.73/5.41mm	RG58, 59, 62, 6
	5133C1 336C1	3C1	.068"/.216"/.324"/.360" 1.73/5.49/8.23/9.14mm	RG58, 59, 62, 6
	5133C2 336C2	3C2	.68"/.262"/.324"/.360" 1.73/6.65/8.23/9.14mm	CATV"F" Connectors RG59, 6



	5132E 236E	2E	AWG 22/20/18/16/14/12 DIN 0.5/0.75/1.0/1.5/2.5/4mm ²	Pin terminal insulated or non-insulated ferrules 
	5132E1 236E1	2E1	AWG 10/8/6 DIN 6/10/16 mm ²	Pin terminal insulated or non-insulated ferrules 
	5132E2 236E2	2E2	AWG 22/20/18/16/14/12/10/8/6 DIN 0.5/0.75/1.0/1.5/2.5/4/6/10/16 mm ²	Pin terminal insulated or non-insulated ferrules 
	5132E3 236E3	2E3	AWG 22/20/2/18/16/14/12/10 DIN 0.5/0.75/1.0/1.5/2.5/4/6 mm ²	Pin terminal insulated or non-insulated ferrules 
	5132F 236F	2F	AWG 22-18/16-14 DIN 0.5-1.0/1.5-2.5 mm ²	Insulated flag terminal 
	5132F1 236F1	2F1	AWG 22-18/16-14 DIN 0.5-1.0/1.5-2.5 mm ²	Non insulated flag terminal 
	5132H 236H	2H	AWG 22-18/16-14/12-10 DIN 0.5-1.0/1.5-2.5/4-6 mm ²	Insulated terminal 
	5132N 236N	2N	AWG 20-18/16-14/12-10/8 DIN 1.5/2.5/6/10 mm ² JIS 1.25/2.0/5.5/8 mm ²	Non-insulated terminal 
	5132R 236R	2R	AWG 22-18/16-14/12-10 JIS 1.25/2.0/5.5 mm ²	Vinyl insulated w/o copper sleeve 
	5132U 236U	2U	AWG 14-22 DIN 2.5-0.5 mm ²	Non-insulated, open barrel & d-sub V.35 terminal 
	5132W 236W	2W	AWG 22-18/16-14/12-10 DIN 0.5-1.0/1.5-2.5/4-6 mm ²	Insulated terminal 