


(Scale: 1.2: 1)

Cell(电芯): LP603449 Date code(喷码): Inner controlling standard(内控标准)

Battery Specification (电池参数)	Min Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single battery capacity (单体电池容量)	1000	PCM protection (保护板参数)	Overcurrent Detection(A) (过流值)	2-6
	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single battery capacity (单体电池容量)	1100		Overcharge Detection Voltage(V) (过充保护电压)	4.28±0.05
	Normal Voltage 标称电压 (V)	3.7		Overdischarge Detection Voltage(V) (过放保护电压)	2.3±0.1
	Internal impedance 内阻 (≦) (mΩ, AC 1KHZ)	200		Charge Temp. 充电温度 (°C)	0-45
Ambient Conditions (工作环境)		Discharge Temp. 放电温度 (°C)		-20-60	
Humidity(湿度)		Humidity(湿度)		65±20%	

Remark(备注):  
1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).  
2. Rohs compliant(严格按照ROHS要求生产).



Title	LP603449-PCM-NTC-LD/	Draft:	Approved:	Revise No.:	E4-2009
File NO.	A01560		Moyongdi	Projection:	1/1
			Rosa	Page:	1/1
			Keyan	Scale:	1:1
		Draw Date:	09/12/04	Unit:	mm