



## LITE-RACK Fibre Lite Card Cage

### Product Features

- 19 inch rack mount, 2U
- Accommodates up to 16 cards
- Built-in switch-mode power supply
- Built-in redundant power supply
- All Fibre Lite cards are hot-swappable
- 5 year warranty



\* Fibre Lite transmission cards sold separately

Fibre Lite Card Cage	<b>LITE-RACK</b>
<b>Product Description</b>	Fibre Lite Card Cage
<b>Technical Specifications:</b>	
<b>General</b>	
Power supply:	220Vac
Power consumption:	85 watt
Operating temperature:	-30°C to 50°C
Operating humidity:	0% to 95%; non-condensing
Slots:	16
Dimensions (mm):	482 x 300 x 88

Designed for the following products:

Ordering information:	PVTX-010-RMM	Fibre Lite - Single channel video transmitter; cage card
	PVTX2-010-RMM	Fibre Lite - Two channel video transmitter; cage card
	PVRX-010-RMM	Fibre Lite - Single channel video receiver; cage card
	PVRX2-010-RMM	Fibre Lite - Two channel video receiver; cage card
	PDTX-010-RMM	Fibre Lite - Single channel data transmitter; cage card
	PDRX-010-RMM	Fibre Lite - Single channel data receiver; cage card
	PVTXD-010-RMM	Fibre Lite - Video transmitter with data receiver; cage card
	PVRXD-010-RMM	Fibre Lite - Video receiver with data transmitter; cage card
	PATX2-010-RMM	Fibre Lite - Two channel audio transmitter; cage card
	PCTX5-010-RMM	Fibre Lite - Five channel contact closure transmitter; cage card
	PCR5-010-RMM	Fibre Lite - Five channel contact closure receiver; cage card

\* Product specifications are subject to change without notice

\* All rights remain reserved