High Performance Thermal Imager

The Major Tech MTi13 high performance thermal imager is affordable and makes preventative maintenance quick & easy!



Technical Datasheet

MTi13

MTi13

The MTi13 Thermal Imager with 80 x 80 resolution at 50Hz offers real-time capture and a large touch screen with a toolbar that will assist you to fine-tune and analyze images quickly. Temperature range from -20°C to 350°C, 20X continuous zoom, picture-in-picture, Hot/Cold spot marker, voice comment recording and text annotation on images.















Features:

- 80 x 80 Resolution
- Real time capture
- 2.8" LCD display with touch screen
- Focal length 9mm
- Field of view 17x17°
- Minimum focus distance 0.5m
- Spatial resolution 3.78mrad
- Thermal sensitivity / NETD < 0.1° C /100mK
- Temperature -20°C 350°C
- Picture-in-Picture
- Text annotaion on images
- Voice comment recordings
- 32X Continuous Digital Zoom 5 Megapixels Digital Camera
- Area Min / Max with Auto Hot / Cold Spot Mark
- USB interface with 8GB Micro SD card

IR Resolution : 80 x 80 pixels

FPA / Spectal Range : Uncooled microbolometer / 8-14ym

RANGE

Focul length 9mm

Specifications

FUNCTION

Image modes

Field of view (FOV) 17° x 17° / 0.5m

Spatial resolution (IFOV) 3.78mrad Thermal sensitivity / NETD $: <0.1^{\circ}\text{C} @ +30^{\circ}\text{C} (+86^{\circ}\text{F}) / 100\text{mK}$

Image Frequency : 50Hz

Focus mode Manual

Zoom 1-32 x continuous, digital zoom

IR image, Visual image,

: Picture-in-Picture Picture-In-Picture

IR area on visual image Color palettes Iron, Rainbow, Grey, Grey Inverted Temperature range

-20°C - 150°C (-4°F - 302°F)

0°C - 350°C (+32°F - 662°F)

Accuracy : ±2°C or ±2% of reading Spotmeter

Center Spot, Auto hot or cold markers Storage media 8GB Micro SD Card Video storage format : MPEG 4 > 60 minutes Image storage format : JPEG > 1000 pictures **Built-in digital camera**

: 5 Mega pixels Built-in digital lens data FOV 59 Interfaces

USB-mini / Audio / HDMI Video out

: HDMI POWER SYSTEM Li-ion / 4 Hours **Battery** In camera (AC adapter) **Charging system** Automatic shutdown Power management 224 x 77 x 96mm Size (L x W x D)

: 500g Weight



Full Infrared



Picture-in-Picture



Colour Alarms



Full visible light

Applications

- Plant / General Maintenance
- HVAC/R
- Transportation / Automotive
- **Cooling and Reheating**
- Serving areas and Cold storage
 - Food service equipment

Standard Accessories

- **Carry Bag**
- 7.5mm Lens
- Sun visor
- Battery
- Charger
- Camera lens cap
- Software
- Handstrap
- **USB** cable

RCA cable