

ME-1000-WPTU  
ME-2000-WPTU  
ME-3000-WPTU

ME-6000-WPTU  
ME-10000-WPTU

## ONLINE UPS



ME-6000-WPTU  
ME-10000-WPTU

ME-3000-WPTU

ME-2000-WPTU

ME-1000-WPTU

### Features

- True double-conversion online UPS
- Wide input voltage range (110-300 VAC)
- Input power factor correction 0.99
- Output power factor 0.8
- Converter mode available
- ECO mode operation for energy saving (only available for 1-3KVA)
- Generator compatible
- Adjustable battery numbers only available for 6K and up models
- Smart SNMP works well with either USB or RS-232 together
- Emergency power off function only available for 6K and up models

MODEL	ME-1000-WPTU	ME-2000-WPTU	ME-3000-WPTU	ME-6000-WPTU	ME-10000-WPTU
PHASE	Single phase with ground				
CAPACITY	1000 VA / 800 W	2000 VA / 1600 W	3000 VA / 2400 W	6000 VA / 4800 W	10000 VA / 8000 VA
<b>INPUT</b>					
Voltage Range	Low Line Transfer	160 VAC/140 VAC/120 VAC/110 VAC ± 5% (Ambient Temp.<35°C) (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)		176 VAC ± 3% @ 100% load 110 VAC ± 3% @ 50% load	
	Low Line Comeback	175 VAC /155 VAC/ 135 VAC /125 VAC± 5 % (Ambient Temp.<35°C) (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)		186 VAC ± 3% @ 100% load 120 VAC ± 3% @ 50% load	
	High Line Transfer	300 VAC ± 5 %		300 VAC ± 3%	
	High Line Comeback	290 VAC ± 5 %		290 VAC ± 3%	
Frequency Range	40Hz ~ 70 Hz			46~54 Hz or 56~64 Hz	
Power Factor	≥ 0.99 @ nominal voltage			≥ 0.99 @ 100%load	
<b>OUTPUT</b>					
Output Voltage	200/208/220/230/240 VAC			208/220/230/240 VAC	
AC Voltage Regulation (Batt. Mode)	± 1%			± 1%	
Frequency Range (Synchronized Range)	47 ~ 53 Hz or 57 ~ 63 Hz			46~54 Hz or 56~64 Hz	
Frequency Range (Batt. Mode)	50 Hz ± 0.25 Hz or 60Hz ± 0.3 Hz			50 Hz ± 0.1 Hz or 60 Hz ± 0.1 Hz	
Current Crest Ratio	3:1			3:1	
Harmonic Distortion	≤ 3 % THD (Linear Load), ≤ 6% THD (non-linear load)			≤ 3 % THD (Linear Load) ≤ 5 % THD (Non-linear Load)	
	Transfer Time	AC Mode to Batt. Mode Inverter to Bypass			Zero Zero
Waveform (Batt. Mode)	Pure Sinewave				
<b>EFFICIENCY</b>					
AC Mode	88%	89%	90%	92%	93%
Battery Mode	83%	87%	88%	90%	91%
<b>BATTERY</b>					
Battery Type	12V/9Ah	12V/9Ah	12V/9Ah	12V/9Ah	12V/9Ah
Numbers	2	4	6	16	16
Typical Recharge Time	4 hours recover to 90% capacity			9 hours recover to 90% capacity	
Charging Current (max.)	1.0 A			1.0 A / 2.0 A (adjustable)	
Charging Voltage	27.4VDC ± 1%	54.7VDC ± 1%	82.1VDC ± 1%	218.4 VDC ± 1%	218.4 VDC ± 1%
<b>INDICATORS</b>					
LCD Panel	UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions				
<b>ALARM</b>					
Battery Mode	Sounding every 4 seconds				
Low Battery	Sounding every second				
Overload	Sounding twice every second				
Fault	Continuously sounding				
<b>PHYSICAL</b>					
Dimension, D x W x H (mm)	282 x 145 x 220	397 x 145 x 220	421 x 190 x 318	369 x 190 x 688	442 x 190 x 688
Net Weight (kgs)	9.8	17	27.6	61	66
<b>ENVIRONMENT</b>					
Humidity	20-90 % RH @ 0- 40°C (non-condensing)			0-95 % RH @ 0- 50°C (non-condensing)	0-95 % RH @ 0- 40°C (non-condensing)
Noise Level	Less than 50dB @ 1 Meter			Less than 55dB @ 1 Meter	Less than 58dB @ 1 Meter
<b>MANAGEMENT</b>					
Smart RS-232/USB	Supports Windows <sup>®</sup> 2000/2003/XP/Vista/ 2008, Windows <sup>®</sup> 7/8, Linux, Unix, and MAC				
Optional SNMP	Power management from SNMP manager and web browser				

NOTE 1: Derate to 80% of capacity in CVCF mode or when the output voltage is adjusted to 200/208VAC.

NOTE 2: If the UPS is installed or used in a place where the altitude is above than 1000m, the output power must be derated one percent per 100m.

Distributed by