



**ROCKER SWITCH MODEL: MR-3**  
 RATING: 10A 125/250VAC (cURus)  
 10(4)A 250V~ T85 (FI/ENEC)  
 DIELECTRIC STRENGTH: 1000VAC FOR 1 MINUTE  
 INSULATION RESISTANCE: 500VDC 100MΩ (MIN)  
 CONTACT RESISTANCE: 20mΩ INITIAL (MAX)

**MR323-C6BB**



X(CUTOUT DIMENSION)	Y(CUTOUT DIMENSION)	Z(PANEL THICKNESS)
19.2 <sup>+0</sup> <sub>-0.1</sub> mm	12.9 <sup>+0.15</sup> <sub>0</sub> mm	0.75~1.25mm
19.4 <sup>+0</sup> <sub>-0.1</sub> mm	12.9 <sup>+0.15</sup> <sub>0</sub> mm	1.25~2mm
19.8 <sup>+0</sup> <sub>-0.1</sub> mm	12.9 <sup>+0.15</sup> <sub>0</sub> mm	2~3mm

PANEL CUTOUT DIMENSION TABLE

NOTE: TOLERANCES UNLESS OTHERWISE SPECIFIED: ±.012/0.3 (in/mm)

REVISION	DESCRIPTION	REVISED BY	TOLERANCES		ANGLE		SCALE	UNIT	PART NAME	PART NO	DWG NO
			DRAWN BY	CHECKED BY	DESIGNED BY	APPROVED BY					
2021.05.20	首次出圖	达志各	达志各				2/1	mm	MR-3 SPEC DRAWING	MR-3-23S-C6-BBNWC	S8446A