

## NVR XY5516 POE 5,0MP

System	Main processor	Hi3536
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/9/16
Video	Video input (IP)	8*4K/16*5M/16*3M
	Access bandwidth	192Mbps
	Forwarding bandwidth	153Mbps
	Video compression	H.265/H.264
	Display quality	Max:4K
	Playback quality	4K/5M/3M
	Decode	2*4K/4*5M/8*3M
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	support
record &play back	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local payback	2*4K/4*5M/8*3M
	Search mode	Search by Time/Calendar/Event/Channel
	Record storage	HDD、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA , 1ch HDMI HD output
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port , 16 POE ports

## NVR XY5516 POE 5,0MP

	USB interface	2*USB2.0 ports
	HDD	4 SATA
	ESATA	No
	POE	16 ports
	ONVIF	Support