

CVI/TVI/AHD IR SPEED DOME

- * **4.5 inch Outdoor High mini Speed Dome camera**
- * **10Xoptical zoom 5-50mm Optical zoom**
- * **Real time transmission,lossless video**
- * **High definition1080P**
- * **Long distance transmission up to 500 meters**
- * **OSD IR distance 50M**
- * **Total Metal body construction, IP66 rate protection**
- * **IR illumination & power consumption is variable dependant on zoom factor**

Specification

Camera	
Sensor	1/3" progressive scan CMOS
Effective pixels	1080P(1080X1980)
Total pixels	2.0MP
Lens	10X optical zoom
Iris	F1.6 ~F2.8
View of Angle	H : 51.8° (W) ~ 5.86° (T) V : 39.1° (W) ~ 4.4° (T)
Min. illumination	Color: 0.1 Lux \ B/W: 0.01Lux
WDR	Digital WDR
BLC	On / Off
Picture Effects	Auto / Color / B & W / Negative
D/N	IR-CUT
S/N Ratio	≥50dB
Dome	
Pan range	360°continuous rotation
Tilt range	0°~93°
Manual Pan speed	0.02~200°/S
Manual Tilt speed	0.02~90°/S

Preset Points	128
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Outdoor: -40°~ +60°
Operation mode	English
Pan and Tilt	Support
Humidity	≤95% Non Condensing
Power	DC12V
Consumption	≤15W
Lightning Protection	Transient voltage 6000V
Video interface	CVI/TVI/AHD
Communication	RS485 (+/-)/ Coaxial Cable
Connection	Coaxial Cable
Related validation	IP66,CE,FCC,RoHs
IR parameters	
Auto Control	PWM
LED	Array 42Mil 6PCS
IR distance	Up to 50 meters
Support ambient light detection	IR illumination on 1-15 grades selectable;