

1of2//TECHNICAL DATA

Edition 1: 05/07/2016

ROC SERIES

IP66 POLYESTER DOUBLE INSULATION BOXES

Description: IP66 - POLYESTER BOX WITH POLYCARBONATE OPAQUE LID - MOD.: Reference: ROC42PO

4x2

Characteristics:

Product type: Polyester double insulation box with opaque cover

Dimensions cabinet: (AxBxC) 360x180x171 mm

Installation: Surface

Type of door: Opaque polycarbonate lid

Locking: Sealable screws for use with a screwdriver

Finish: Fibreglass-reinforced hot-pressed polyester

Colour: RAL 7035 grey

Mounting plate: Without mounting plate

Weight (Kg): 0,6

Materials: Base in polyester - Transparent lids made of polycarbonate UV.

Technical data:

Degree of protection: IP66
Resistance to impact: IK09

Ambient temperature range: -40°C / +100°C

Maximum operating voltage: -

Certificates and standards:

Directive: 2014/35/EU

Standards: UNE-EN 62208 / UNE-EN 61439-1 (as applicable)

Certificates:

 ϵ



2of2//TECHNICAL DATA


Edition 1: 05/07/2016

ROC SERIES

IP66 POLYESTER DOUBLE INSULATION BOXES

Description: IP66 - POLYESTER BOX WITH POLYCARBONATE OPAQUE LID - MOD.: 4X2

Reference: ROC42PO





Pictures and drawings are standards. To get more details please surf www.ide.es to download those files (pdf, dxf, igs).

Dimensions cabinet: [AxBxC] 360x180x171 mm

Cable entry:

Body to be flush-fitted:

Wall fixing: (GxH) 335x155 mm

Inside usable space: (DxExF) 340x160x154 mm

Sustainability:

Product end of life:

RoHS - REACH

It does not require specific recycling operations.

Supply:

Supplied in a single box per packaging multiples. Each reference includes a bag with four standard manual closing screws and four screws for fixing to the base plate.