

SLP-275 V/1+1

Ordering number 8595090519485


SPD type 2 - Surge Arrester

pluggable module, visual fault signalling, module locking


combination of varistor surge arrester and encapsulated spark gap, connected in the 1+1 mode, installation to LV installations, especially to sub-distribution boards in TT and also TN-S systems, for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages



Dimension drawing



Basic circuit diagram



Technical specifications

Type of SPD	T2
Nominal voltage	U _n 230 V AC
Maximum operating voltage L-N	U _c 275,00 V AC
Maximum operating voltage N-PE	U _c 255,00 V AC
Nominal discharge current (8/20 µs) L-N	I _n 20,00 kA
Nominal discharge current (8/20 µs) N-PE	I _n 20,00 kA
Maximum discharge current (8/20 µs) L-N	I _{max} 40,00 kA
Maximum discharge current (8/20 µs) N-PE	I _{max} 40,00 kA
Voltage protection level at 5 kA L-N	U _p 0,90 kV
Voltage protection level mode L-N	U _p 1,35 kV
Voltage protection level mode N-PE	U _p 1,50 kV
Voltage protection level mode L-PE	U _p 1,50 kV
Ability to independently switch off the following current N-PE	I _f 0,1 kA
Short-circuit current rating	I _{SCCR} 50,0 kA
Maximum overcurrent protection	160 A gL/gG
Response time L-N	t _a 25 ns
Response time N-PE	t _a 100 ns
TOV 5 s L-N	335 V withstand
TOV characteristic (TOV 5 s)	withstand
TOV 120 min L-N	440 V safe failure
TOV characteristic (120 min)	safe failure
TOV 200 ms L-PE	1 455 V
TOV 200 ms N-PE	1 200 V
TOV characteristic (TOV 200 ms)	withstand
Cross-section of connected conductors solid (min)	1,00 mm ²
Cross-section of connected conductors solid (max)	35,00 mm ²
Cross-section of connected conductors stranded (min)	1,00 mm ²
Cross-section of connected conductors stranded (max)	25,00 mm ²
Fault indication L-N	red indication field
Fault indication N-PE	no
Degree of protection	IP 20
Range of ambient temperatures - min	-40 °C
Range of ambient temperatures - max	80 °C
Mounting	DIN rail 35 mm

According to standard

EN 61643-11:2012, IEC 61643-11:2011

Plug module

SLP-275 V/0

ETIM Class

EC000941