

# SN-IPR54/03AQDN Day/Night Mini Bullet with IR LED



## Key features

- Day/Night Mini Dome with IR LEDs
- Vandal Resistant IK6 & IP66 Weatherproof
- Fixed 3.6Lens / Multi Angle installation

## Free Software for Mobile (Android / iPhone / iPad)

Remote setup of camera, fully live display of camera.

Works over LAN / WAN (Internet) connection.



## Software

100% fully functional IP camera with multi browser support, Onvif Profile S supports motion detection & edge recording. Embedded Flash video technology inside camera. Supporting PoE or 12v power for all installation types. Supplied with NVR Software supporting up to 64 Channels\* Safari, Chrome, IE, Firefox, Opera, all browser compatible!



\*Cameras recording in real-time depends on PC Specifications.

## Specifications

Parameter	Details
<b>CAMERA</b>	
Sensor	Aptina 1/3" CMOS
Max Resolution / FPS	1280x720 / 30fps with eWDR @ 70dB
Min. illumination	0.2Lux @ F1.2 (Color) (0 Lux IR LED On)
Day / Night	True Day / Night with ICR Filter.
IR LEDs	2pc Super Flux IR LED 850nm for 10-15 Meters (33 feet)
Lens	3.6mm Fixed Mega Pixel IR Coated. Angle 89°±4°(D)x 70°(H)x 51.9°(V)
Video Output	n/a
Electronic Shutter	Auto / User 1/5 - 1/50, 0000; 50/60Hz software selectable.
<b>PARAMETERS</b>	
Compression	H-264 High Profile (Support Baseline Profile) / MJPEG
Bit Rate (CBR/VBR)	Stream1 200Kbps - 8Mbps ; Stream2 100Kbps - 6Mbps ; Stream3 (Fixed)
Quality Setting	1 - 9 (9 Highest)
Multi- Streaming	User setting of Stream 1/2 at supported Resolutions, Stream3 MJPEG Stream
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102db
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas < 8% of total picture
<b>NETWORK</b>	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 Profile-S Listed
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish
Recording Simultaneous.	Remote FTP server, TCP/UDP CMS, RTSP connection (stream 1,2 or 3)
Network Protocols:	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP. Unicast and Multicast supported.
Memory Card Slot	n/a
<b>CABLE</b>	
Network	RJ45 Socket from camera on dangle cable. With PoE
Power	DC power socket on dangle cable if no PoE available 12v Only
<b>GENERAL</b>	
Power	12V DC @ 1A (IR LED On) / PoE Class 3 on Ethernet
Temperature	Operating: -40°F to 122°F (-40°C to 50°C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP66 / IK10
Product Dimensions	169mm x 70mm x 63mm ( 6.6" x 2.75" x 2.5")
Product Weight	0.3kg / 0.66lb