

SN-IPD54/31VDR 3Axis Dome / Audio / PoE / MicroSD Slot



Key features

- 3Axis Dome / Audio / PoE / MicroSD Slot
- Alarm & Audio In & Out on cable
- ICR Day / Night with 3.3-12mm DC Iris Lens

Free Software for Mobile (Android / iPhone / iPad)

Remote setup of camera, fully live display of camera.
Works over LAN / WAN (Internet) connection.



Software

100% fully functional IP camera with multi browser support, Onvif Profile S supports motion detection & edge recording. Embedded Flash video technology inside camera. Supporting PoE or 12v power for all installation types. Supplied with NVR Software supporting up to 64 Channels* Safari, Chrome, IE, Firefox, Opera, all browser compatible!



*Cameras recording in real-time depends on PC Specifications.

Specifications

Parameter	Details
CAMERA	
Sensor	Aptina 1/3" WDR CMOS
Max Resolution / FPS	2048x1536 / 30fps
Min. illumination	0.5Lux @ F1.2 (Color) (0 Lux IR LED On)
Day / Night	True Day / Night with ICR Filter.
IR LEDs	Works with external IR Lighting
Lens	3.3-12mm Vari-focal IR Corrected DC Auto IRIS
Video Output	Internal Service RCA output for BNC Video with IP Address OSD
Electronic Shutter	Auto / User 1/5 - 1/50, 0000; 50/60Hz software selectable.
PARAMETERS	
Compression	H-264 High Profile (Support Baseline Profile) / MJPEG
Bit Rate (CBR/VBR)	Stream1 50Kbps - 12Mbps ; Stream2 10Kbps - 6Mbps ; Stream3 (Fixed)
Quality Setting	1 - 9 (9 Highest)
Multi- Streaming	User setting of Stream 1/2 at supported Resolutions, Stream3 MJPEG Stream
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102db
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas < 8% of total picture
IR	12pcs super flux IR LED for 20meters IR distance
NETWORK	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 Profile-S Listed
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish, (European Languages coming 2013)
Recording Simultaneous.	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection (stream 1,2 or 3)
Network Protocols:	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP. Unicast and Multicast supported.
Memory Card Slot	Internal memory card supports Max 64GB. Supports Edge Recording
AUDIO	
Input / Output	Inbuilt Microphone Cable 1 x RCA Input / 1 x RCA Output @ 1v Line Level
Audio Compression	G711 A-Law, G711 U-Law, RAW_PCM
GENERAL	
Power	12V DC @ 300mA / PoE Class 3 on Ethernet
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant
Product Dimensions	130 x 112 mm (5.1 x 4.4)
Product Weight	0.45kg / 1lb