ReneSola

Off Grid Module

80W

Easy Installation and Handling for Various Applications

Conforms to IEC 61215:2005, IEC 61730:2004 PV Standards

ISO9001, OHSAS18001, ISO14001 Certified





Mechanical Characteristics

Cell Type	**Polycrystalline 156 x 93 mm**
Glass	**High Transmission, Low Iron, Tempered Glass, thickness 3.2mm**
Frame	**Anodized Aluminum Alloy**
Junction Box	**10A Bypass Diodes**
Dimensions	***905 x 668 x 35 mm**
Output Cable	**500 mm**
Weight	**7.2 kg**
Installation Hole Location	**See Drawing Above**

Electrical Characteristics STC RS-SL80TU-18P

Maximum Power (Pmax)	**80W**
Power Tolerance	**0 ~ +3%**
Module Efficiency	**13.23%**
Maximum Power Current (Imp)	**4.38 A**
Maximum Power Voltage (Vmp)	**18.25 V**
Short Circuit Current (Isc)	**4.69 A**
Open Circuit Voltage (Voc)	**21.96 V**

Guarantee

10-year *material & workmanship*

25-year *power output*

Characteristics

Temperature Coefficient of Voc	**-0.38%/°C**
Temperature Coefficient of Isc	**0.04%/°C**
Temperature Coefficient of Pmax	**-0.47%/°C**
Nominal Operating Cell Temperature (NOCT)	**47°C±2°C**

PV CYCLE

ReneSola.com