

HellermannTyton

TBU13X

TBU Software

- Optical interface adaptor
- USB Cable and software

Free Software updates available: www.brymen.com/product-html/software-download/ General purpose Dimensions: 250(L) x 150(W)

TRRUSB

• Dimensions: 250(L) x 150(W) x 60(H)





Cable & Software Specification	
Cable & Software (USB PLUG)	DMM
TBU20X	TBM251/252/255/257
TBU86X	TBM811/812/525/829/867/869
	Clamp
TBU13X (Serial and USB Adaptor)	TBM135/157/189
TBRUSB (USB Adaptor)	Fits all TBR RS232 serial plugs

Understanding Measurement Categories:

CATIV

Category IV (Primary supply level) is for measurements performed at source of low voltage installation. Examples are electricity meters and measurements on primary over-current protection devices and ripple control units.





Category I (Signal level) is for measurement of electronic equipment.

Calibration Certificate:

• Certificate where all the parameters are checked against its specification


Certificate of Conformance:



lied With

Certificate normally issued by the manufacturer that states the instrument meets its specifications IEC (International Electrotechnical Commission) is an international safety standard for electrical equipment.

TBU86X



Calibrations available:

SANAS (South African National Accreditation System):

- Full SANAS certificate is a calibration where all the parameters are checked against its specifications
- Partial SANAS certificate is a calibration where some of the parameters are checked against its specifications