



TLVD17

- Non-contact voltage detection
- Sensitivity adjustable
- LED and tone indication
- Identifies live and neutral

Technical Overview

Voltage (AC)	5V - 1000V
Frequency	50 - 500Hz

Model Specification

Power Source	1 x AAA 1.5V Battery
Certificates	CE EN:61010-1, EN:61326-1

CAT IV ⚡ 1000V



TLVD18

- Direct contact voltage and non-contact voltage detection
- LED and tone indication
- Detect Voltage in lighting fixtures and circuit breakers
- Detect a break in a wire
- Flash light

Technical Overview

AC Direct Contact Voltage (V)	50V - 600V
AC Non-contact Voltage (V)	50V - 600V
Frequency (Hz)	50Hz - 500Hz
Operating Temperature (°C)	0°C to 40°C
Operating Humidity	< 80% Relative Humidity
Altitude	Max 2000m

Model Specifications

Power Source	2 x 1.5 AAA Batteries
Certificates	EN 61010-1, EN 61326-1

CAT III ⚡ 600V



WIBRETEST

- Industrial Heavy Duty
- AC/DC
- Neon Indication (Green, Red)
- Polarity
- Oil resistant

Technical Overview

Voltage Range (V)	110 - 750V AC/DC
-------------------	------------------

Model Specification

Power Source	No batteries required
Optional Accessories	Wibreneon (spare neon)

CAT IV ⚡ 300V