

Specifications	Range	Best Accuracy
Model		UT211A
AC Current (A)	600mA/6000mA/60A	$\pm(1.5\%+10)$
AC Voltage (V)	6V/60V/600.0V/600V	$\pm(0.8\%+3)$
DC Voltage (V)	600V	$\pm(0.7\%+5)$
	6V/60V/600.0V/600V	$\pm(0.7\%+3)$
Resistance (Ω)	600 Ω /6K Ω /60K Ω /600K Ω /6M Ω /60M Ω	$\pm(0.8\%+2)$
Capacitance (F)	6nF/60nF/600nF/6 μ F/60 μ F/600 μ F/6mF/62mF	$\pm(4\%+5)$
Features		
Display Count		6000
Auto Range		√
True RMS		√
Diode	Around 3.0V	√
VFC		√
NCV		√
Auto Power Off	Around 15 minutes	√
Continuity Buzzer		√
Low Battery Indication	$\leq 2.5V$	√
Data Storage		
Zero Mode		
LCD Backlight		√
Input Protection		

Input Impedance for DCV	$\geq 10M\Omega$	√
General Characteristics		
Power	AAA 1.5V x 2	
LCD Size	39.3mm x 26.5 mm	
Product Color	Red and Grey	
Product Net Weight	170g	
Product Size	175mm x 60mm x 33.5mm	
Standard Accessories	Batteries, Test Lead, Bag	
Standard Individual Packing	Gift Box, Carrying Bag, English Manual	
Standard Quantity Per Carton	40pcs	
Standard Carton Measurement	395mm x 390mm x 185mm	
Standard Carton Gross Weight	13.72kg	