

VC-016R 16 Channel CAT5e UTP Passive Video Transceiver

Product Features

- Up to 4 CCTV camera images on a single CAT5e cable
- Formats supported:
 - Analogue composite video
 - HD-CVI 1920H (1920x1080)
 - HD-CVI 1280H (1280x720)
- Exceptional interference rejection
- Benefits:
 - Lower cable costs
 - Lower labour costs
 - Lower conduit and cable path costs
 - Faster installation process



***one VC-01 required per camera

Passive Video Balun	VC-016R	
Product Description	16 Channel Passive Video Balun for HD-CVI and Analogue Cameras	
Technical Specifications:		
Video Input / Output		
Video input / output:	Analogue Video: 1 Volt p-p, 75 Ohm	HD-CVI: 1920H (1920X1080), 1280H (1280X720), 75 Ohm
Bandwidth:	DC - 6MHz	
Connector:	16 Female BNC	
UTP Input / Output		
Video input / output :	100 Ohm balanced	
Connector:	Sixteen 2-way removable screw terminals	
CAT5e cable length:		
Analogue video:	300m	
HD-CVI 1920H:	200m	
Cable supported:		
CAT5e:	Solid copper	
CAT6:	Solid copper	
General		
Operating temperature:	-20°C to 50°C	
Operating humidity:	0% to 95%; non-condensing	
Dimensions (mm):	(L) 19 inch rack mount x (H) 1 and 1/2 U x (W) 30mm	

***CCA cable not supported

