

VC-01PM CAT5e UTP Passive Video Transmitter with DC Power for HD-CVI and Analogue Cameras


Product Features

- Video and power for the camera over one CAT5e cable
- Formats supported:
 - Analogue composite video
 - HD-CVI 1920H (1920x1080)
 - HD-CVI 1280H (1280x720)
- Superb colour video quality up to 300m
- Exceptional interference rejection
- Benefits:
 - Lower cable costs
 - Lower labour costs
 - Lower conduit and cable path costs
 - Faster installation process



Passive UTP Transmitter	VC-01PM	
Product Description	Single channel passive UTP video transmitter with power output for HD-CVI and Analogue Cameras	
Technical Specifications:		
Video input / Power output		
Video input:	Analogue Video: 1 Volt p-p, 75 Ohm	HD-CVI: 1920H (1920X1080), 1280H (1280X720), 75 Ohm
Bandwidth:	DC - 6MHz	
Video input connector:	BNC	
Power output:	12Vdc, 500mA	
Power output connector:	2-way removable screw terminal	
UTP Input / Power Output		
Video output:	100 Ohm balanced	
Power input:	30Vdc	
Connector:	4-way removable screw terminal	
Cable supported:		
CAT5e:	Solid copper	
CAT6:	Solid copper	
General		
Operating temperature:	-30°C to 50°C	
Operating humidity:	0% to 95%; non-condensing	
Dimensions (mm):	93 x 29 x 50	

***CCA cable not supported



* Product specifications are subject to change without notice
* All rights remain reserved