

ITEM		XY IPCAM30 MP SD64
Image Sensor	Image sensor	1/4" Color CMOS Sensor
	Display	1280x720 (Mage Pixels)
	Lens	f:3.6mm, F:2.4 (IR Lens)
	Mini.illumination	0.5 Lux
Lens	Lens Type	Glass Lens
	Viewing Angle	60 Degree
Audio	Microphone	Audio of two way
Domain name	Server	P2P Server/ DDNS server
Video	Image Compression	H.264 MJPEG
	Image Frame Rate	15 FPS(VGA),30FPS(QVGA)
	Resolution	1280x720(720P), 640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Rtical / Horizontal
	mode	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
Communication	Ethernet	One 10/100Mbps RJ-45
	Supported Protocol	HTTP/DHCP/IP/TCP/UDP/FTP/SMTP/DDNS/PPPoE/UPnP
	Mobilephone monitor	Support Iphone/Ipad/3G phone/smartphone
	Wireless Standard	IEEE 802.11b/g/n
	Wireless Standard	802.11b:11Mbps(max.) 802.11g:54Mbps(max.)
	Wireless Security	64/128-bitWEP Encryption
Physical	Pan/Tilt Angle	Horizontal:300° & Vertical: 120°
	Infrared Light	12 IR LEDs, Night visibility up to 15 Mete
	Product size	95(L) x100(W) x125mm(H)
	Gross Weight	542g/pcs (packing size:196x165x123mm)
	Net Weight	320g/pcs (only product)
Power	Specification	DC 5V/2.5A 1.5 meter
	Power Consumption	5 Watts
Environment	Operate Temper	0° ~ 55°C (14°F ~ 122°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temper	-10°C ~ 60° (14°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
PC Requirements	CPU	2.0GHZ or above (suggested 3.0GHZ)
	Memory Size	512MB or above (suggested 1.0GHZ)
	Display card	64M or above
	Supported OS	Microsoft Windows XP/Vista/Windows7
	Browser	IE 6.0, IE7.0 IE8.0 firefox2.0 firefox3.0 .Google

Certification	CE,FCC,RoHS
----------------------	-------------