

ITEM		XY IPCAMOD07
Image Sensor	Image sensor	1/4" Color CMOS Sensor
	Display	1280x720(Mega Pixels)
	Lens	f:3.6mm, F:2.4 (IR Lens)
	Mini.illumination	0.5 Lux
Lens	Lens Type	Glass Lens
	Viewing Angle	60 Degree
Audio	Microphone	Not
Domain name	Server	P2P Server
Video	Image Compression	H.264
	Image Frame Rate	15 FPS(VGA),30FPS(QVGA)
	Resolution	1280x720(720P), 640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	mode	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
Communication	Ethernet	One 10/100Mbps RJ-45

	Supported Protocol	HTTP/DHCP/IP/TCP/UDP/FTP/SMTP/DDNS/PPPoE/UPnP
	Mobilephone monitor	Support iPhone/iPad/3G phone/Android smartphone
	Wireless Standard	IEEE 802.11b/g/n
	Wireless Standard	802.11b:11Mbps(max.) 802.11g:54Mbps(max.)
	Wireless Security	64/128-bitWEP Encryption
Physical	Pan/Tilt Angle	Fixed
	Infrared Light	Night visibility up to 20 Mete
	Product size	
	Gross Weight	
	Net Weight	
Power	Specification	DC 5V/2.5A 1.5 meter
	Power Consumption	5 Watts
Environment	Operate Temper	0° ~ 55°C (14°F ~ 122°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temper	-10°C ~ 60° (14°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing

PC Requirements	CPU	2.0GHZ or above (suggested 3.0GHz)
	Memory Size	512MB or above (suggested 1.0GHz)
	Display card	64M or above
	Supported OS	Microsoft Windows XP/Vista/Windows7
	Browser	IE 6.0, IE7.0 IE8.0 firefox2.0 firefox3.0 .Google
Certification	CE,FCC,RoHS	