



Specification XY-AHD151CPD PROMO 2.0MP 4IN1 Model Sensor 1080P CMOS Image Sensor System PAL PAL:1920(H)*1080(V) Picture Elements 2.0 Megapixel Horizontal Recolution Video OutPut **Hybrid Video Output** S/N Ratio ≥48dB 0.05LUX(without IR LED) Min.Illumination Electronic Shutter 1/50(1/60)S~1/100,000S White Balance Auto >0.45 Gamma Ratio 3.6mm 3MP lens Lens Mount -10°C ∼ +50°C Operating Temp. 0 to 95%RH(non-condensing) Humidity **DC 12V** Power/Current Sync System 2:1 Interlace internal Sync. English OSD Language 10M / 24 units IR LED Night vision Outdoor/Indoor Indoor Packing list Model Number Name Digital CCTV Camera XY-AHD151CPD PROMO 2.0MP 4IN1 1 XY-AHD151CPD PROMO 2.0MP 4IN1 **Jser Manual**

Changing the Setting on 4 in 1 camera

Hold button for 5 seconds according to table below to change setting.

Once set, remove power - Unit will now remain on new setting.

BIITEOHOIT	UP	DOWN		RIGHT
VIDEO	AHD	CVI	TVI	ANALOGUE(CVBS)

Note: Camera default setting is AHD.

Method to change to TVI:

Hold button to LEFT for approx 5 sec, (no need to press button down), camera will switch to TVI, pull out power from camera, camera will remain set to TVI.

Method to change to Analog (CVBS):

Hold button to RIGHT for approx 5 sec, camera will switch to Analog, pull out power from camera, camera will remain set to Analog.

Method to change to CVI:

Hold button to DOWN for approx 5 sec, camera will switch to CVI, pull out power from camera, camera will remain set to CVI.





Notes:

*Please Please note the camera's operating temperature and its working environment. Avoid using the camera at too high or too low temperatures.

*Never install the camera facing the direct sunlight or bright object. otherwise damge to the CCD will occur.

*Dont mount the camera near a radiator or heater.