	La
Model	XY-IP CAM1000BV(A) 5.0MP POE
Camera	
Image sensor	5.0MP 1/2.5" SC335E Low illumination CMOS sensor
Min.illumination	Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR
	black/white 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s - 1/10,000 s
day/night	Support IR-CUT
Noise Reduction	Support 2D/3D
WDR	Digital
LED	2 units powerful Array LED
Distance	35M IR distance
Lens	2.8~12mm 5 Megapixel lens
Video & Audio	compression
Video	H.265AI/H.265+ (Compatible with H.265/H.264), support dual stream, AVI;
Bite rate	0.1M~10Mpbs variable;1~30f/s variable
Audio	G.711,audio&video synchronization
Audio interface	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input; 0ch
	output(expandable to 1ch)
lmage	'
Max.image	
resolution	5MP 2592*1944@15fps
Image Output:	Main stream: 5MP 2592*1944@15fps;4MP 2560*1440@20fps; 2MP
	1920*1080@20fps;
	sub-stream: 704*576@25fps;
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client
Network	
Intelligence	Supporting human detection and tripping line detection, and supports intelligent functions such as customized face detection, number statistics, etc.
Net interface	1*RJ45 10/100M adaptive Ethernet port;support RTSP/FTP/DHCP/NTP/UPnP etc
Reliability	Comprehensive lightning protection, 7 * 24 hours-10°C ~ 65°C high temperature stable and reliable testing
Onvif	Yes
Others	Support WEB,OSD,live video transmission,motion detect and IO alarm,front-end
	storage/playback/download, and center reminder and image linkage,support JPEG
	capture; united remote client monitoring sofaware、MYEYE;perfect SDK
Mobile Monitoring	Support multiple mobile monitoring (iOS, Android)
General	
Operating condition	humidity less than 90%(non-condensing)
COHUITION	

Power supply	DC12V ±10% / PoE
Weight	1000g