


Model	XY-IPCAM 771BVF 2.0MP POE
Photo	
Camera	
Image sensor	1080P 2.0MP CMOS sensor
Min illumination	Color 0.1Lux @ (F1.2, AGC ON),0 LUX with IR black/white 0.01 Lux @ (F1.2, AGC ON),0 LUX with IR
Shutter	1/50(1/60)s - 1/10,000 s
day/night	Support IR-CUT
LED	42 units F5 LED
Distance	30M IR distance
Lens	2.8~12mm Megapixel lens
Compression	
Video	H.265, support dual stream, AVI,
Bite rate	100 Kbps~8Mbps
Audio compression	G.711a, support bidirectional talk, audio & video synchronization
Audio interface	1ch input, level:2Vp-p, impedance:1kΩ, support sound pick-up input;1ch output, impedance:16Ω,30mw, support microphone
Image	
Max image resolution	1920*1080, 2.0 megapixel
Image output	Main stream: 1920*1080@20fps, 1280*720@25fps; Sub stream: 704*576@25fps
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client
Network	
Storage	Network storage
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Basic	anti-flicker, dual-stream, heartbeat, password protection
Net interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc
General	
Operating condition	humidity less than 90% (non-condensing)
Power supply	DC12V ±10% + PoE
Weight	800g