

CA 14

Electrical characteristics

Range of resistance values	100Ω... 5MΩ Lin (A) 1 KΩ ... 2.2 MΩ Log (B) Antilog(C) Others, upon request
Tolerance	100Ω ... 1MΩ ±20% >1MΩ ... 5MΩ ±30% Others, upon request
Variation laws	Lin (A), Log (B), Antilog (C) Others, upon request
Residual resistance	Lin (A), Log (B), Antilog (C) $\leq 5 \times 10^{-3} R_n$ R _n Minimum value 2Ω
CRV - Contact Resistance Variation (dynamic)	Lin (A) $\leq 3\% R_n$
Contact resistance (static)	Lin (A) $\leq 5\% R_n$
Maximum power at 40° C.	Lin (A) 0,25W No Lin (B,C) 0,13W
Maximum voltage	Lin (A) 250 V No Lin (B,C) 200V
Operating temperature	(-25°C ... +70°C) Others, on demand
Temperature coefficient	100Ω ... 10KΩ: +200/-300 p.p.m. >10KΩ ... 5MΩ: +200/-500 p.p.m.

Mechanical Characteristics

Resistive element	Carbon film
Wiper torque	0,5 ... 2,5 Ncm
Rotation angle (mechanical)	265° ± 5°
Rotation angle (electrical)	245° ± 20° Others, upon request
Torque at end stop	10 Ncm
Max. push and pull on the rotor	50 N
Cycles	1000, more cycles available on request.