

Specification		
	Model	DVR XY 9108H
System	Main chip	Hi3531A
	OS	LINUX
	System Resources	Multi-channel Realtime recording, Multi-channel playback, Multi-channel
Interface	Operation menu	16-bit true color graphical menu interface, mouse operation supported
	Display	1/4 display (take the pure coaxial input mode as an example)
Video	Format	H.264
	Output	VGA、HDMI (Max up to 1080P)
	Preview	8*5M@20fps(AHD)/ 8*3M@18fps(AHD)/8*1080P (5 in 1)
	Recode	8*5M@11fps(AHD)/ 8*3M@10fps(AHD)/8*1080P@12fps(5 in 1)/ 8*720P@12fps(5 in 1)
	Decord	4*5M@8fps(AHD)/ 4*3M@10fps(AHD)/4*1080P@12fps(5 in 1)/ 8*720P@12fps(5 in 1)
	Multi-mode Input	AHD: 8*5M; Hybrid: 4*5M (CVBS) +4*5M (IP) NVR: 8*1080P+8*960P;4*3M;4*5M
	Motion Detect	Each view window can set 192 (16*12) detection area,can set multi
Audio	Audio	G.711A
	Intercom	Support
Record and Playback	Recording mode	Manual、Alarm、Motion Detect、Timer
	Local playback	4 Channel (when Analog mode)
	Video search	Time, Date,Event,Channel search
Storage and Backup	Storage	Local HDD, Network
	Backup	Network backup, external HDD, USB Drive, HDD
Port	Video Input	8 * BNC
	Video Output	1 * VGA, 1 * HDMI
	Spot Monitor	no
	Audio Input	4 * RCA
	Audio Output	1 * RCA
	Alarm Input	8 channels
	Alarm Output	1 channel
	Network port	RJ45 10M/100M
	PTZ Control	1 * RS485 Support multipal PTZ Contract

	USB port	2 * USB Port
	HDD Port	2 * SATA hdd ports (up to 6T for each one)
	Wireless Port	3G、WIFI(can be USB WIFI Dongle)
Others	Power	1*HDD: 12V/2A 2*HDD: 12V/5A 1 * HDD with screen: 12V /
	Power consumption	Less than 15W (no HDD)
	Working temperature	0℃—+55℃
	Working humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa
	packageingSize	56.7*36.7*32.6cm
	Weight	12.5kg