

XY IPCAM31

Product Specifications		
	Item	XY IPCAM31
Image Sensor	Sensor	1/5" Color CMOS Sensor
	Display	640 x 480 (300K Pixels)
	Lens	f:3.6mm, F:2.4 (IR Lens)
	Mini.illumination	0.5 Lux
Lens	Lens Type	4-9MM Zoom Lens
	Viewing Angle	60 Degree
Audio	Microphone	Not
Domain name	Server	MSN server/ DDNS server
Video	Image Compression	MJPEG
	Image Frame Rate	15 FPS(VGA),30FPS(QVGA)
	Resolution	640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	mode	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
Communication	Ethernet	One 10/100Mbps RJ-45
	Supported Protocol	HTTP/DHCP/IP/TCP/UDP/FTP/SMTP/DDNS/PPPoE/UPnP
	Mobile phone monitor	Support iPhone/iPad/3G phone/Smartphone
	Wireless Standard	IEEE 802.11b/g
	Wireless Standard	802.11b:11Mbps(max.) 802.11g:54Mbps(max.)
	Wireless Security	64/128-bitWEP Encryption
Physical	Pan/Tilt Angle	Horizontal:360° & Vertical: 90°
	Infra red Light	22 IR LEDs, Night visibility up to 20 Mete
	Product size	205(L) x220(W) x120mm(H)
Power	Specification	DC 5V/2.5A 1.8 meter
	Power Consumption	5 Watts
Environment	Operating Temperature	0°~ 55°C (14°F~122°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temperature	-10°C ~ 60° (14°F ~140°F)
	Storage Humidity	0% ~ 90% non-condensing
PC Requirements	CPU	2.0GHZ or above (suggested 3.0GHz)
	Memory Size	512MB or above (suggested 1.0GHz)
	Display card	64M or above
	Supported OS	Microsoft Windows XP/Vista/Windows7
	Browser	IE 6.0, IE7.0 IE8.0 firefox2.0 firefox3.0 .Google
Certification	CE,FCC,RoHS	