

| <b>Specifications</b>           |                              |
|---------------------------------|------------------------------|
| <b>Model</b>                    | <b>79 1414 15 05</b>         |
| <b>Connector Locking System</b> | <b>Screw-locking</b>         |
| <b>Termination</b>              | <b>Moulded on Cable</b>      |
| <b>Wire gauge (mm)</b>          | <b>0.25 mm<sup>2</sup></b>   |
| <b>Wire gauge (AWG)</b>         | <b>24</b>                    |
| <b>Cable Outlet</b>             | <b>-</b>                     |
| <b>Cable Length</b>             | <b>5m</b>                    |
| <b>Degree of Protection</b>     | <b>IP 67</b>                 |
| <b>Mechanical operation</b>     | <b>&gt;500 mating cycles</b> |
| <b>Upper Temperature</b>        | <b>70</b>                    |
| <b>Lower Temperature</b>        | <b>-25</b>                   |
| <b>Rated Voltage</b>            | <b>125</b>                   |
| <b>Rated Impulse Voltage</b>    | <b>1500</b>                  |
| <b>Pollution degree</b>         | <b>1</b>                     |
| <b>Over Voltage category</b>    | <b>II</b>                    |
| <b>Material group</b>           | <b>III</b>                   |
| <b>Rated Current (40°C)</b>     | <b>3 A</b>                   |
| <b>Volume Resistivity</b>       | <b>&lt;3 mOhm</b>            |
| <b>Material of contact</b>      | <b>CuSn (bronze)</b>         |
| <b>Contact plating</b>          | <b>Au (gold)</b>             |
| <b>Material of contact body</b> | <b>PBT (UL 94 V-0)</b>       |
| <b>Material of housing</b>      | <b>PBT (UL 94 V-0)</b>       |