

Specifications	
Model	DVR XY7016
Housing Height	1U
Operation System	Linux
Video Format	
Video Input	16 channels video Input
Video Output	BNC video output / 1 VGA output
Audio Input	16 channels audio input
Audio Output	1 BNC audio output
Voice Talk	3.5mm Mic Interface
Playback	4 channel
Total Frames	PAL:400fps/NTSC:480fps
Compression Algorithm	Video: H.264 / Audio: G.711 or G.722 or G.726
Record Resolution	CIF: PAL (352x288), NTSC (352x240)
Preview Resolution	4CIF(PAL:704x576,NTSC:704x480) VGA: Up to 1360x768
Dual Stream	Yes
Image Quality	6 levels optional
E-mail Alarm	
HDD	2 SATA interfaces (Each HDD can max support 2000GB)
Alarm Input	16 alarm inputs
Alarm Output	2 alarm outputs
Backup Interface	USB2.0 / High Speed SATA / Remote Backup
Mobile View	Supporting: Windows Mobile,Symbian,Blackberry and iPhone System
Network Interface	RJ45 10M/100M Ethernet Interface
I/O Interface	RX485/RS485, RS485 for PTZ ; USB for Mouse
Other Functions	Watchdog / Dual Stream / PPPoE / DHCP / DDNS
Power Supplier	220±30% V, 50±3% Hz or 110±20% V, 60±3% Hz
Power Consumption	11W (without hard disk)
Work Temperature	-10degC +55degC
Working Humidity	10% ~ 90%
Dimension	405x310x55mm
Gross weight	5.5KG (without hard disk)