

PTZ IP CAM AV322

SPECIFICATIONS	
Model	PTZ IP CAM AV322
Network	
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Frame Rate	NTSC:30, PAL:25
Number of Online Users	10
Security	Multiple user access levels with password
Web management software	YES (Control up to 16 network cameras simultaneously)
Video / Audio	
Video Compression	MPEG4 / MJPEG
Video Remote Contro	YES
Video Adjustment	Brightness, Contrast, Saturation and Hue
Audio Compression	uLaw, 128kbps
Audio Input	External Microphone Input
Camera	
Image Sensor	1/4" Sony Colour Super HAD CCD
Pixels	768(H)x494(V)<NTSC> / 752(H)x582(V)<PAL>
Resolution	480TV lines
Lens	f3.9 ~ 85.9mm
F-number	F1.6 (Wide) ~ 3.7 (Tele)
Viewing Angle	4° ~ 60°
Pan Range	360°
Tilt Range	90°
Zoom	22X Optical Zoom (f3.9 ~ 85.9mm)
Max Speed	Pan 360°/s, Tilt 90°/s
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.
Min Illumination	1 Lux / F1.6
Video Output	1.0 Vp-p. 75Ω
BLC	On / Off
White Balance	White Balance Auto / Indoor 1 / Indoor 2 / Sun / Cloud * Indoor1 = 9000K; Indoor2 = 3000K; Sun = 5500K; Cloudy = 7000K
Camera ID	0~255
Others	
Remote Control	YES
Motion Detection	YES
Alarm and event Notification	Image upload over FTP and email
General I/O	Alarm in x1
Power	12VDC, 1.5A
Operating Temperature	0°C ~ 40°C
Humidity	85.00%
Minimum Web Browsing Requirements	·Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD ·256 MB RAM ·AGP graphics card , Direct Draw, 32MB RAM ·Windows XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later ·Internet Explorer 6.x or later
Dimensions (mm)	145(D) x 184(H)
In/Out Door Use	Outdoor