

Specification				
Model	XY-AHD771BSVF 1080P			
System	PAL			
Picture Elements	PAL:1920(H)*1080(V)			
Horizontal Recolution	2.0 Megapixel			
Video OutPut	Hybrid Video Output			
S/N Ratio	≥48dB			
Min.Illumination	0.0001LUX @ color mode			
Electronic Shutter	1/50(1/60)S ~ 1/100,000S			
White Balance	Auto			
Gamma Ratio	> 0.45			
Lens Mount	2.8~12mm 2MP lens			
Operating Temp.	10°C ~ +50°C			
Humidity	0 to 95%RH(non-condensing)			
Power/Current	DC 12V			
Sync System	2:1 Interlace internal Sync.			
IR Project Distance	no LED			
IR Status	/			
Outdoor/Indoor	Outdoor			
Packing list				
Name	Model	Number		
Digital CCTV Camera	XY-AHD771BSVF 1080P	1		
User Manual	XY-AHD771BSVF 1080P	1		

# Changing the Setting on 4 in 1 camera

Hold button for 5 seconds according to table below to change setting.

Once set, remove power - Unit will now remain on new setting.

DIRECTION VIDEO	UP	DOWN	RIGHT	LEFT
VIDEO	CVI	TVI	AHD	ANALOGUE (CVBS)

## Note: Camera default setting is AHD.

#### Method to change to TVI:

Hold button to left for approx 5 sec, (no need to press button down), camera will switch to TVI, pull out power from camera, camera will remain set to TVI.

### Method to change to Analog (CVBS):

Hold button to RIGHT for approx 5 sec, camera will switch to Analog, pull out power from camera, camera will remain set to Analog.

#### Method to change to CVI:

Hold button to DOWN for approx 5 sec, camera will switch to CVI, pull out power from camera, camera will remain set to CVI.

<u>/!</u> Notes:

\*Please note the camera's operating temperature and its using environment.Avoid using the camera at too high or too low temperatures. \*Never make the camera face the sun or bright object. otherwise will damge the CCD.

\*Dont mount the camera near by the radiator or heater.