

VC-08PR & VC-016PR CAT5e UTP Passive Video Receiver with DC Power

Product Features

- Video and power for the camera over one CAT5e cable
- Formats supported:
 - Analogue composite video
 - HD-CVI 1920H (1920x1080)
 - HD-CVI 1280H (1280x720)
- Superb colour video quality up to 300m
- Exceptional interference rejection
- Benefits:
 - Lower cable costs
 - Lower labour costs
 - Lower conduit and cable path costs
 - Faster installation process



***one VC-01PM transmitter required per camera

Passive UTP Receiver	VC-08PR	VC-016PR
Product Description	8 or 16 channel passive UTP video receiver with power output for cameras	
Technical Specifications:		
Video		
Video output:	Analogue Video: 1 Volt p-p, 75 Ohm	HD-CVI: 1920H (1920X1080), 1280H (1280X720), 75 Ohm
Bandwidth:	DC - 6MHz	
Connectors:	8 BNC	16 BNC
UTP Input / Power Output		
Video input:	100 Ohm balanced	
Power Output:	30Vdc, 500mA per output	
Connector:	8x 4-way removable screw terminal	16x 4-way removable screw terminal
Cable supported:		
CAT5e:	Solid copper	
CAT6:	Solid copper	
General		
Power supply:	220Volt AC (3 pin 16A RSA male plug to female kettle plug power cord supplied)	
Operating temperature:	-30°C to 50°C	
Operating humidity:	0% to 95%; non-condensing	
Dimensions:	(L) 19 inch rack mount x (H) 2U x (W) 214mm including connectors	

***CCA cable not supported

