


Model	XY-IPCAM 4MP30FD H.265
Photo	
<b>Camera</b>	
Image sensor	1/3"OV4689 low illumination CMOS + Hi3516D processor
Min.illumination	Color 0.01Lux @(F1.2,AGC ON),0 LUX with IR black/white 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s - 1/10,000 s
day/night	Support IR-CUT
LED	30 units F5 LED
Distance	10~15M IR distance
Lens	3.6mm 5Megapixel lens
<b>Compression</b>	
Video	H.265/H.264 dual stream
Bite rate	100 Kbps~10Mbps
Audio	G.711, support bidirectional talk, audio & video synchronization
<b>Image</b>	
Max.image resolution	Main stream: 4MP 2592*1520@15fps, 3MP 2048*1536@25fps Sub stream: 704*576@25fps
Frame rate	50Hz:25fps(2048*1536) ; 60Hz:30fps(2048*1536)

Image setting	Saturation, brightness and contrast are adjustable through IE browser or client
<b>Network</b>	
Storage	network storage
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPOE,SMTP,NTP(HTTPS, RTP/RTSP, SIP ,802.1x,IPv6 )
Basic	anti-flicker, dual-stream, heartbeat, password protection
Net interface	One RJ45 10M/100M
<b>General</b>	
Operating condition	humidity less than 90%( non-condensing)
Power supply	DC12V ±10%
Weight	1000g