

A-A SECTION


Specifications
rating : 100V AC MAX or 12V DC 2A MAX
contact resistance : 50mΩ MAX at DC 1A
insulation resistance : MIN 200MΩ at 250V DC
voltage withstand : 250V AC, 1 minute

No.	Description	Material	Treat	Q'ty
10	Contact Terminals	Brass	Silver Ptd.	4
9	4P Housing	PBT		1
8	Cable Tie	Brass	Tin Ptd.	1
7	Shield Cover B	Brass	Nickel Ptd.	1
6	Shield Cover A	Brass	Nickel Ptd.	1
5	Spring	Steel		1
4	Perch	POM		1
3	Strain Boot	PVC		1
2	Holder	ABS		1
1	Shell Cover	ABS		1


COMMUNICA (PTY) LTD
 A WORLD OF ELECTRONICS Reg. No. 1979/00371707

■ HEAD OFFICE
 Tel (012) 657-3500
 Fax (012) 657-3550
 E-Mail: sales@communicaco.za

品名: 4P MINI POWER DIN
 ITEM : CABLE PLUG LUCK TYPE
 料號: XSP42
 PART NO



一般公差
 .X +/-0.25
 .XX +/-0.10



單位: mm
 比例: 3:2

日期: '07/01/23
 版本: V. 1.0

繪圖: DanielShyr
 核准: SkyShyr
 drwn by: aprvid by: